

NUTS

These are detachable nuts which are convenient, reusable and easy to use. Just the nut along with ferrule SC112 makes an entire fitting. The nuts manufactured basically emphasize on 1/16" OD, as this is the most used and standard OD.

Making of fittings with these nuts and ferrules is very easy and hardly takes seconds to replace them.

Making nuts and ferrules detachable brings down tubing assemblies to reduce its price.

TECHNICAL SPECIFICATIONS

SNO	TUBING	PORT	Pressure	Head Style	M.O.C
1	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Flush Nuts	SS, ETFE, Nylon(customizable)
2	1/16" OD	10-32 Flat- Bottom	upto 172bar	Standard	ETFE, Nylon(customizable)
3	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Standard	ETFE, Nylon(customizable)
4	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Standard	ETFE, Nylon(customizable)
5	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Standard	ETFE, Nylon(customizable)
6	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Standard	ETFE, Nylon(customizable)
7	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Short	ETFE, Nylon(customizable)
8	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Standard	ETFE, Nylon(customizable)
9	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Standard	ETFE, Nylon(customizable)
10	1/16" OD 1/8" OD	1/4-28 Flat- Bottom	upto 138bar	Headless	ETFE, Nylon(customizable)